



## LENO system

semi-recessed


**EN** Low profile recessed mounted luminaire, 15 mm visible height; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; designed for continuous lighting systems; surface powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering

**IT** Apparecchio da incasso ultrapiatto da 15 mm di altezza visibile; per montaggio a parete o soffitto; per montaggio in cemento a vista o stuccato, in costruzioni di cartongesso e in pareti o soffitti intonacati; per sistemi di file continue; verniciatura a polvere; inserto luce anti-caduta in profilo di alluminio estruso, fissaggio nel canale con magnete senza bisogno di utensili; luce convogliata lateralmente e direzionata in basso con sistema LGP-Body (Light Guiding Prism) e riflettore ad alta efficienza; diffusore satinato (a filo o sporgente) o con struttura a microprismi a illuminazione omogenea in PMMA; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  80, 3 SDCM  
 up to 137 lm/W  
 L90 @ 50 000 h  
 DALI-2  
 opal, microprismatic ( $UGR \leq 19$ ),  
 jut-out

### Types



### Colours




### Light distributions



DiiA® standards  
 251, 252, 253



single luminaire  
 (p. 496)



microprismatic  
 $UGR \leq 19$



quick  
 installation

## Order options

<b>COLOUR TEMPERATURE</b>	☼☼
3000K	5
4000K	6

### CONTROL

DALI-2

### MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

### LIGHT OPTIC COVER



opal high performance	H
microprismatic (UGR ≤ 19)	G
jut-out	J

## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 90

## Technical data



**LENO semi-recessed,**  
microprismatic, 19.1W, 4000K

### ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8


### CALCULATION SURFACE .....

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E <sub>m</sub> )	> 500 lx
Uniformity (U <sub>0</sub> )	> 0.6

### GLARE EVALUATION

Table Classification X=4H   Y=8H   S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

**LUMINOUS FLUX** value calculated for  
colour white, cover opal  
microprismatic -5%, jut-out-4%



## LENO semi-recessed

### INSTALLATION CHANNEL

TYPE	L (mm)	ORDER CODE
channel	613	051-892006
channel	1221	051-892012
channel	1830	051-892018
channel	2438	051-892024

order installation channel, light inset + mounting accessories separately



### LIGHT INSET


SYSTEM POWER	L (mm)	ORDER CODE
10.8W	612*	051-8112::37
191W	1220	051-8214::37
28.6W	1828	051-8216::37
38W	2436	051-8218::37

\*only available as end unit

COVER	COLOUR TEMP.	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
opal high	3000K	17.6 W/m	2010 lm/m	129 lm/W
performance	4000K		2130 lm/m	137 lm/W
microprismatic	3000K	17.6 W/m	1900 lm/m	122 lm/W
UGR ≤ 19	4000K		2010 lm/m	129 lm/W
jut-out	3000K	17.6 W/m	1930 lm/m	124 lm/W
	4000K		2040 lm/m	131 lm/W

## Accessories

### END CAPS



TYPE	ORDER CODE
end caps mounting housing (pair)	051-8996210
end caps semi-recessed	051-899221

### LINEAR CONNECTOR




TYPE	ORDER CODE
linear connector (pair)	051-8992110
linear connector (10 pairs)	051-8992110.10

### POWER FEEDER CONNECTOR 220-240 V | 13A



TYPE	ORDER CODE
power feeder connector	051-8992330

### CONCRETE MOUNTING HOUSING



L (mm)	UNIT	ORDER CODE
616	end	051-8960060
1224	start/end	051-8960120
1221	middle	051-8961120
1833	start/end	051-8960180
1830	middle	051-8961180
2441	start/end	051-8960240
2438	middle	051-8961240

### DISMOUNTING TOOL



TYPE	ORDER CODE
vacuum cup	086-30000