

TASK

table


^{EN} Desk lamp in puristic design with high functionality; lamp head 360° rotatable and +/- 15° tiltable; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; continuously adjustable dimming via optical sensor (10-100% analog); integrated USB charging socket for charging of a smart device; version with presence detector

▮ Apparecchio da scrivania di design sobrio ed elevata funzionalità; testata girevole di 360° e orientabile di +/- 15°; verniciatura a polvere; distribuzione della luce diretta con sistema LGP-Body (Light Guiding Prism); luce convogliata lateralmente e direzionata in basso tramite incisione laser; illuminazione assolutamente omogenea; LED ad efficienza energetica con elevata resa cromatica; dimming continuo con sensore ottico (10-100% analogico); con porta USB per caricare smart devices; modello con segnalatore di presenza

Quickinfo

3000K, 4000K
CRI ≥ 90, 3 SDCM
up to 92lm/W
L90 @ 50000h
DIM via optical sensor (10–100%)
presence sensor
opal

Type




Colours




Light distribution



direct



360° rotatable,
± 15° tiltable



presence
sensor



USB charging
socket

Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

MATERIAL COLOUR	
○ pure white RAL 9010	7
● jet black RAL 9005	8

LIGHT OPTIC COVER



opal

Options on request


COLOUR RENDERING INDEX
CRI ≥ 80

MOUNTING

table clamp, wall fastening



TASK table



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11W	3000K	950lm	0 5 9 - 2 8 1 1 1 :: 7 <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	4000K	1010lm	

Accessories

BASE PLATE

TYPE	Ø-H (mm)	ORDER CODE
base plate	Ø 220·13	0 5 9 - 2 8 9 1 1 1 <input checked="" type="checkbox"/>

TABLE CLAMP for hole Ø68 mm, 10–30 mm range

TYPE	Ø-H (mm)	ORDER CODE
table clamp	Ø 75·77–88	0 5 9 - 2 8 9 2 1 1 <input checked="" type="checkbox"/>