

## VITA

wall

**EN** Luminaire housing, mounting channel and front cover from extruded aluminium profile, angular version; extremely slim luminaire housing (only 25 mm), for direct/indirect radiation characteristic; no visible screws; surface anodised; suitable for wall mounting; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for optimised light control and homogeneous illumination; lighting modules in aluminium, powder coated; CRI ≥ 90 or XPECTRUM; incl. 2 converters for separate control of the direct/indirect light component; energy-efficient LEDs with very good colour rendering

**IT** Corpo illuminante, canale di montaggio e copertura frontale in profilo di alluminio estruso, modello squadrato; corpo dell'apparecchio estremamente sottile (solo 25 mm), per un fascio di luce diretto/indiretto; nessuna vite visibile; superficie anodizzata; montaggio a parete; inserti luminosi con riflettori asimmetrici lucidi appositamente calcolati, cover prismatiche lineari incl. pellicola con diversa distribuzione della luce per la componente diretta o indiretta della luce, per un controllo della luce ottimizzato e un'illuminazione omogenea; inserti luminosi in alluminio verniciato a polvere; CRI ≥ 90 o XPECTRUM; incl. 2 convertitori per il controllo separato della componente della luce diretta/indiretta; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo


3000 K, 4000 K  
CRI ≥ 90, CRI ≥ 98 XPECTRUM  
up to 7200 lm/m  
L90 @ 50 000 h  
DALI-2  
reflector

### Types

horizontal mounting





vertical mounting




### Colour



### Light distributions



system  
solution



CRI ≥ 98  
XPECTRUM

## Order options

<b>COLOUR TEMPERATURE</b>	☼☼
3000 K (CRI ≥ 90)	0
4000 K (CRI ≥ 90)	1
3000 K (CRI ≥ 98 XPECTRUM)	Y
4000 K (CRI ≥ 98 XPECTRUM)	Z

## CONTROL

### DALI-2

direct/indirect separately controllable

## MATERIAL COLOUR

● anodised aluminium

## LIGHT OPTIC

reflector/linear prismatic

## Options on request

### COLOUR TEMPERATURE


tunable white (2700–6500 K)

### MATERIAL COLOUR

white, black, special colours

### SPOTLIGHT ALIGNMENT

SPOTLIGHT for reading




## VITA wall



### DIRECT/INDIRECT - HORIZONTAL MOUNTING


SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
128 W	4000 K	4320 lm	1013	099-9136☼☼36A
152 W	4000 K	7200 lm	1213	099-9137☼☼36A



### DIRECT/INDIRECT - VERTICAL MOUNTING

SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
128 W	4000 K	4320 lm	1013	099-9166☼☼36A
152 W	4000 K	7200 lm	1213	099-9167☼☼36A

## Light distribution



reflector  
direct/indirect

**LUMINOUS FLUX** value calculated for  
4000 K, CRI ≥ 90, white;  
3000 K CRI90-9%, 3000 K CRI98 -24%,  
4000 K CRI98 -22%